

Private Mobile Radio

stabo ATP 10 VHF
136-174 MHz

stabo ATP 40 UHF
400-470 MHz

*with powerful
lithium ion battery
&
charging cradle*

meets IP54

16 Channels

2 Programmable Keys (SK1 and SK2)

Emergency Function

TX Power switchable (High/Low)

Speech Announcement

CTCSS / CDCSS

VOX Function (9 levels)

PTT ID Encode/DTMF

Squelch (9 levels)

Scan Function

Dual Watch

TOT

Battery Power Indication

Battery low Warning

Software Programming

Specifications

General

Mode	F3E (FM)
Channel spacing	12,5 kHz/20 kHz
Power consumption	TX 1.3 A, RX 0.3 A
Dimensions	60 x 105 x 33 mm without antenna
Weight	225 g incl. Li-Ion battery+ antenna
Li-Ion battery pack	1600 mAh/7.4 V

Transmitter

Transmit. pwr. Lo/Hi 1/5 W ATP 10, 1/4 W ATP 40

Receiver

Sensitivity -121 dBm (0,2µV) 20 dB SINAD
AF output power 700 mW with 16 ohms



CE 0700 ⓘ

	Art. no.
stabo ATP 10	01725
stabo ATP 40	01726

optional accessories	Art. no.
Loudspeaker microphone	50122
security headset	50124
boom earphone/micro	50125
VOX headset	01811
programming kit	01814
nylon carrying case	50121
Li-Ion battery pack 1600 mAh/7.4V	01813

Notified in D. Licence and fee required!

Errors and technical modifications reserved. Copyright © 10/2012 stabo Elektronik GmbH

stabo Elektronik GmbH · 31137 Hildesheim, Germany · Münchwiese 14-16 · Telefon +49 (0) 5121 7620-10 · Telefax +49 (0) 5121 516847

Internet: www.stabo.de · e-mail: info@stabo.de