

stabo multifon security IV

video security system with intercom

... tap-proof, protected against interference

with weatherproof (IP65) camera

Scope of Supply:

DVR color monitor with mounting bracket
wireless color camera (IP 65) with mounting bracket
power supply for monitor 5 V/2 A
power supply camera 9 V/0.6 A
RJ45 cable
User manual (DE/EN)

Art.-Nr. 51086

Specifications

Monitor

Frequency	2400 ~ 2483,5 MHz
Data rate	4 Mbps
Sensitivity	- 81 dBm
Modulation	GFSK with FHSS
Display	17.8 cm (7") TFT LCD
Image resolution	H: 800 RGB V: 480
Angle of view	H: 140° V: 110°
Image res. of AV output	VGA 640x480/10 fps, QVGA 320x240/20 fps
Operating voltage	5 V DC 2 A
Input current	1050 mA max.
Working temp. range	- 10°C ~ 40°C
Working humidity range	no more than 85% RH
Dimensions (H x W x D)	182 x 138 x 35 mm
Weight	467 g

Camera

Frequency	2400 ~ 2483,5 MHz
Data rate	4 Mbps
Modulation	GFSK with FHSS
Transmitting power	16 dBm (TYP)
Image sensor	1/4" CMOS colors
Effective pixels	H:720 V:480
Image res./frame rate	Cam x2: 720p @ 15 fps Cam x2: VGA @ 30 fps Cam x4: VGA @ 15 fps
Objective	3.6 mm / F2.0 (ICR cut filter)
Angle of view (diagonal)	64°
IR LED	24 LEDs/ 850nm
Operating voltage	9 V DC +/- 5%
Input current	450 mA with IR LED, 240 mA without IR LED
Working temp. range	- 10°C ~ 40°C
Protection class	IP 65
Dimensions (H x W x D)	80 x 113 x 120 mm
Weight	290 g with support

Optional accessory

	Art no.
Additional camera (IP 65)	51087
WLAN antenna (s. page 25) for stabo multifon security and WLAN cameras Dimensions: 179 x 208 x 43 mm Weight: 363 g cable length: ca. 100 cm	51085

**nur möglich bei Einsatz von Zusatz-Kameras
with accessory cameras only



Abbildung zeigt Monitor in QuadEinstellung**
Illustration shows monitor in quad mode**

Viewing Talking back Recording 5 seconds pre-recording

- **pre-recording**
(5 Sek. Voraufnahme-Funktion)
- **digitale Funktechnik (2,4 GHz):** sichere, kabellose Übertragung, Schutz der Privatsphäre, geschützt gegen Störungen durch andere Funkanwendungen
- **wetterfeste (IP 65) VGA-Farbkamera**
720p Auflösung
Gegensprechfunktion
24 leistungsstarke Infrarot-LEDs für Nachtsicht
integrierter PIR-Bewegungsmelder
schwenkbarer Halter
(auch für Wand-/Deckenmontage)
- **17,8 cm Farb-Monitor**
Gegensprechfunktion
SD-Karten-Schacht (SD-card bis 64 GB, Karte nicht enthalten)
Quadfunktion**
(bis 4 Kamerabilder gleichzeitig anzeigen)
- **multilinkfähig****
(bis 4 Kameras anschließbar)
- **Reichweite bis 150 m**
(unter optimalen Bedingungen)
- **RJ45 (LAN)-Buchse**
(*für Internetanschluss zur WLAN-Nutzung)
- **Daueraufzeichnung oder Aufnahmeauslösung durch Bewegungsmelder (PIR Sensor) oder Video Motion Detection**
- **Aufnahme für jeden Tag individuell programmierbar**
- **Scan-Funktion**
- **Pre-recording function (5 sec.)**
- **Digital wireless transmission (2.4 GHz)**
provides interference free, safe signals and protects your privacy
- **Weatherproof (IP 65) VGA color camera**
720p resolution
intercom function
24 high-performance infrared LEDs for night vision
integrated PIR sensor for motion detection
swivelling bracket
(also for wall/ceiling fastening)
- **17.8 cm color monitor with intercom function**
SD card slot (for standard SD card with max. 64 GB; card not included)
quad function**
(simultaneous of 4 cameras)
- **Multilink function****
(system expandable up to 4 cameras)
- **Range up to 150 m**
(under optimum conditions)
- **RJ45 (LAN) socket**
(*for internet access to use WLAN)
- **Permanent recording or recording activated by PIR or Video Motion Detection**
- **Recording individually programmable for each day**
- **Scan function**